Z LED Performance

Part of the High/Low Bay product category

Model	Z LED Performance 2 Cool White
Code	AZPELED/2
Application	Ancillary, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	150W
Operating Temp	-30°C - 45°C
Lumens Delivered	23000lm
lm/W	150lm/W
CCT	4000K
UGR	28
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	2.661 kg
Colour / Finish	Black
Diameter	321 mm
Height	180 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.92
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Robust LED low/high bay for industrial, commercial and retail applications
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Alternative installation options by means of drop rods, jack chain and catenary wire
- Additional lens options offer mid (85°) and narrow (55°) beam angles; ideal for racking aisles
- Bracket accessories available for ceiling or wall mounting

ACCESSORIES

AZPELED/FB1	Z LED Performance 1 & 2 Mounting Bracket
AZPELED/REF	Z LED Performance Aluminium Reflector





Z LED Performance

Part of the High/Low Bay product category

Model	Z LED Performance 2 Cool White
Code	AZPELED/2
Application	Ancillary, Hospitality, Industrial, Retail











