Harrier

Part of the Emergency product category

Model	Harrier IP65 Blade Exit Sign
Code	AHARLED/3M/ST
Application	Ancillary, Industrial

GENERAL INFORMATION

Input	220-240V
Operating Temp	0°C - 40°C
Lumens Delivered	130lm (Standard)
CCT	6500K
Beam Angle	110

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.54 kg
Colour / Finish	White
Height	51 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.34
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Selectable self-test/manual test as standard
- Optional hanging blade legends (supplied with self-adhesive legend as standard) for enhanced appearance
- Aesthetically designed for modern appearance
- 20mm side and rear cable entries
- High output LED performance and distribution allows maximum spacing providing reduced cost

ACCESSORIES

AHARLED/ALAR	Harrier IP65 Blade Exit Sign Double Sided Legend Arrow Left and Right
AHARLED/L/AD	Harrier IP65 Blade Exit Sign Double Sided Legend Arrow Down
AHARLED/L/AU	Harrier IP65 Blade Exit Sign Double Sided Legend Arrow Up



Harrier

Part of the Emergency product category

Model	Harrier IP65 Blade Exit Sign
Code	AHARLED/3M/ST
Application	Ancillary, Industrial









