Aztec

5YR IP66 IK08 ON-SITE WARRANTY 3 YEARS

Part of the Floodlights product category

Model	Aztec Asymmetrical Floodlight 50W Photocell
Code	AAZLED50/ASY/PC
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	50W
Operating Temp	-30°C - 40°C
Lumens Delivered	6800lm
lm/W	136lm/W
CCT	5000K
Beam Angle	60/120

MATERIAL INFORMATION

Diffuser Material	Tempered Glass
Product Weight without Packaging	2.122 kg
Colour / Finish	Black
Height	267 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	5
CRI	70
Internal / External	External
Surface / Recessed / Suspended	Pole, Wall
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- High performance die-cast aluminium LED floodlight suitable for industrial applications
- High output, high efficiency asymmetric lens technology for anti-light pollution
- Pre-installed breathable gland prevents internal moisture accumulation
- Bracket design allows installation without removing mounting bracket
- High efficiency up to 143 Lm/W





Aztec

Part of the Floodlights product category

Model	Aztec Asymmetrical Floodlight 50W Photocell
Code	AAZLED50/ASY/PC
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail



